



6.5 JDJ

.264"	6.5mm Spitzer SP Hot- Cor®
Weight (grains)	140
Ballistic Coefficient	0.498
Sectional Density	0.287
COAL Tested	2.700"
Speer Part No.	1441

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Vihtavuori N160	Reformed Winchester	CCI 200	34.5	1998	38.5 C	2230
Alliant Reloder 15	Reformed Winchester	CCI 200	28.5	1938	32.5	2204
IMR 4064	Reformed Winchester	CCI 200	27.5	1894	31.5	2169
Vihtavuori N140	Reformed Winchester	CCI 200	28.0	1897	32.0	2168
Hodgdon H414	Reformed Winchester	CCI 200	31.5	1918	35.5	2162
Accurate 2520	Reformed Winchester	CCI 200	26.5	1873	30.5	2155
Hodgdon H380	Reformed Winchester	CCI 200	31.0	1900	35.0	2145
IMR 4350	Reformed Winchester	CCI 200	32.0	1928	36.0 C	2140
IMR 4320	Reformed Winchester	CCI 200	28.0	1927	32.0	2136
Winchester 760	Reformed Winchester	CCI 200	31.0	1880	35.0	2133
Alliant Reloder 19	Reformed Winchester	CCI 200	33.5	1872	37.5 C	2095
Hodgdon H4831	Reformed Winchester	CCI 200	34.0	1834	38.0 C	2050

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load