



7-30 Waters (Handgun)

| | |
|------------------------------|----------------|
| .284" | 7mm |
| | TNT® HP |
| Weight (grains) | 110 |
| Ballistic Coefficient | 0.384 |
| Sectional Density | 0.195 |
| COAL Tested | 2.550" |
| Speer Part No. | 1616 |

| Propellant | Case | Primer | START CHARGE | | MAXIMUM CHARGE | |
|---------------------------|---------|---------|-----------------|----------------------------|-----------------|----------------------------|
| | | | Weight (grains) | Muzzle Velocity (feet/sec) | Weight (grains) | Muzzle Velocity (feet/sec) |
| Winchester 748 | Federal | CCI 250 | 35.0 | 2191 | 39.0 | 2463 |
| Vihtavuori N135 | Federal | CCI 200 | 31.0 | 2092 | 35.0 | 2462 |
| Accurate 2015 | Federal | CCI 200 | 29.0 | 2253 | 33.0 | 2451 |
| Hodgdon H4895 | Federal | CCI 200 | 32.0 | 2147 | 36.0 | 2449 |
| Hodgdon H335 | Federal | CCI 250 | 32.0 | 2216 | 36.0 | 2422 |
| Alliant Reloder 15 | Federal | CCI 200 | 33.0 | 2079 | 37.0 | 2421 |
| IMR 3031 | Federal | CCI 200 | 30.0 | 2124 | 34.0 | 2376 |
| Accurate 2230 | Federal | CCI 250 | 27.5 | 2163 | 31.5 | 2376 |
| IMR 4895 | Federal | CCI 200 | 30.5 | 2155 | 34.5 | 2375 |

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load