



7mm T/CU

.284"	7mm Spitzer SP Hot- Cor®	7mm Spitzer BTSP
Weight (grains)	130	130
Ballistic Coefficient	0.368	0.424
Sectional Density	0.230	0.230
COAL Tested	2.465"	2.465"
Speer Part No.	1623	1624

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Accurate 2015	Federal	CCI 400	26.0	2116	28.0	2279
Accurate 2230	Federal	CCI 400	27.0	2058	29.0	2210
IMR 4895	Federal	CCI 400	27.2	2030	29.2 C	2201
Hodgdon H322	Federal	CCI 400	25.0	2030	27.0	2192
Vihtavuori N130	Federal	CCI 400	23.0	1984	25.0	2157
Hodgdon H335	Federal	CCI 400	27.4	1999	29.4	2145
Winchester 748	Federal	CCI 400	29.0	1993	31.0	2130
IMR 3031	Federal	CCI 400	26.0	1969	28.0	2120
Hodgdon H4895	Federal	CCI 400	26.5	1968	28.5 C	2117
Hodgdon BL-C(2)	Federal	CCI 400	28.0	1968	30.0	2109
IMR 4198	Federal	CCI 400	21.0	1917	23.0	2100
Alliant Reloder 7	Federal	CCI 400	21.0	1882	23.0	2061

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load