



7mm T/CU

.284"	7mm Spitzer BTSP	7mm Spitzer SP Hot-Cor®	7mm Grand Slam® SP/CANN
Weight (grains)	145	145	145
Ballistic Coefficient	0.472	0.416	0.353
Sectional Density	0.257	0.257	0.257
COAL Tested	2.475"	2.475"	2.475"
Speer Part No.	1628	1629	1632

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Hodgdon H322	Federal	CCI 400	25.0	1961	27.0	2118
Accurate 2520	Federal	CCI 400	27.0	1970	29.0	2116
Accurate 2015	Federal	CCI 400	23.5	1940	25.5	2105
IMR 4895	Federal	CCI 400	26.5	1952	28.5	2099
Hodgdon H4895	Federal	CCI 400	26.0	1941	28.0	2090
Hodgdon BL-C(2)	Federal	CCI 400	27.5	1901	29.5 C	2039
Vihtavuori N130	Federal	CCI 400	22.0	1855	24.0	2024
Hodgdon H335	Federal	CCI 400	26.0	1874	28.0	2018
IMR 3031	Federal	CCI 400	25.2	1868	27.2 C	2016
Winchester 748	Federal	CCI 400	28.0	1856	30.0 C	1989
Alliant Reloder 7	Federal	CCI 400	20.0	1702	22.0	1872

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load