



32-20 Winchester (Contender Only)

.308"	30
	Plinker® SPRN
Weight (grains)	100
Ballistic Coefficient	0.144
Sectional Density	0.151
COAL Tested	1.710"
Speer Part No.	1805

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Hodgdon H110	Winchester	CCI 500	16.0	1734	17.0	1908
Winchester 296	Winchester	CCI 500	15.5	1646	16.5	1897
Accurate No. 9	Winchester	CCI 500	13.0	1666	14.0	1833
IMR 4227	Winchester	CCI 500	15.5	1637	16.5 C	1831
Alliant 2400	Winchester	CCI 500	12.0	1595	13.0	1793
Hodgdon HS-6	Winchester	CCI 500	9.1	1606	10.1	1713
Alliant Herco	Winchester	CCI 500	8.1	1587	9.1	1712
IMR 4198	Winchester	CCI 500	17.0	1527	18.0 C	1683
IMR SR 4759	Winchester	CCI 500	12.0	1326	13.0 C	1582

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load