



## 38 S&W

.358"	38 LSWC	38 LSWC HP	38 LRN
Weight (grains)	158	158	158
Ballistic Coefficient	0.123	0.121	0.170
Sectional Density	0.176	0.176	0.176
COAL Tested	1.065"	1.065"	1.065"
Speer Part No.	4624	4628	4648

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Red Dot	Winchester	CCI 500	2.4	667	2.7	765
IMR SR 7625	Winchester	CCI 500	2.6	683	2.9	752
Alliant Herco	Winchester	CCI 500	2.9	630	3.2	702
Alliant Unique	Winchester	CCI 500	2.8	619	3.1	694
Alliant Bullseye	Winchester	CCI 500	2.2	629	2.4	693
Winchester 231	Winchester	CCI 500	2.3	593	2.6	671

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*