



38 Special

.357"	38 UCHP	38 GDHP SB
Weight (grains)	110	110
Ballistic Coefficient	0.113	0.117
Sectional Density	0.123	0.123
COAL Tested	1.455"	1.455"
Speer Part No.	4007	4009

SHORT BARREL VELOCITIES
Test Firearm: S&W M15 2"

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Unique	Speer	CCI 500	5.4	806	5.8	936
Accurate No. 5	Speer	CCI 500	6.8	860	7.2	900
Vihtavuori 3N37	Speer	CCI 500	6.5	845	6.9	895
Hodgdon H. Universal	Speer	CCI 500	5.1	760	5.5	882
Alliant Power Pistol	Speer	CCI 500	6.2	823	6.6	880
Hodgdon Hi-Skor 700-X	Speer	CCI 500	4.2	784	4.6	879
Alliant Bullseye	Speer	CCI 500	4.2	791	4.6	852
Hodgdon TITEGROUP	Speer	CCI 500	4.1	782	4.5	850
Winchester 231	Speer	CCI 500	4.6	817	5.0	848
Alliant American Select	Speer	CCI 500	DNR	—	4.3	784

DNR — do not reduce

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load