



38 Special +P

.357"	38 JHP	38 GDHP SB
Weight (grains)	110	110
Ballistic Coefficient	0.113	0.117
Sectional Density	0.123	0.123
COAL Tested	1.455"	1.455"
Speer Part No.	4007	4009

SHORT BARREL VELOCITIES
Test Firearm: S&W M15 2"

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Unique	Speer	CCI 500	5.9	929	6.3	976
Hodgdon H. Universal	Speer	CCI 500	5.7	895	6.1	976
Accurate No. 5	Speer	CCI 500	7.5	915	7.9	969
Alliant Power Pistol	Speer	CCI 500	7.0	911	7.4	967
Vihtavuori 3N37	Speer	CCI 500	6.9	903	7.3	958
Hodgdon Hi-Skor 700-X	Speer	CCI 500	4.7	878	5.1	954
Hodgdon TITEGROUP	Speer	CCI 500	4.7	875	5.1	945
Winchester 231	Speer	CCI 500	5.2	884	5.6	944
Alliant Bullseye	Speer	CCI 500	4.8	873	5.2	941
Alliant American Select	Speer	CCI 500	DNR	—	4.8	879

DNR — do not reduce

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load