



## 38 Special +P

.357"	<b>38</b>
<b>Weight (grains)</b>	<b>GDHP SB</b>
<b>Ballistic Coefficient</b>	135
<b>Sectional Density</b>	0.141
<b>COAL Tested</b>	0.151
<b>Speer Part No.</b>	1.450"
	4014

**SHORT BARREL VELOCITIES**  
Test Firearm: S&W M15 2"

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Accurate No. 7	Speer	CCI 500	7.8	838	<b>8.2</b>	882
Accurate No. 5	Speer	CCI 500	6.6	819	<b>7.0</b>	878
Hodgdon HS-6	Speer	CCI 500	6.8	780	<b>7.2</b>	856
Alliant Power Pistol	Speer	CCI 500	6.0	797	<b>6.4</b>	845
Alliant Unique	Speer	CCI 500	4.8	768	<b>5.2</b>	834
Hodgdon H. Universal	Speer	CCI 500	5.0	785	<b>5.2</b>	825
Vihtavuori 3N37	Speer	CCI 500	6.0	760	<b>6.4</b>	823
IMR PB	Speer	CCI 500	DNR	—	<b>4.7</b>	788

DNR — do not reduce

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*