



44 Remington Magnum

.429"	44
Weight (grains)	GDHP
Ballistic Coefficient	210
Sectional Density	0.154
COAL Tested	0.163
Speer Part No.	1.600"
	4428

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Winchester 296	Speer	CCI 350	25.5	1562	27.5	1664
Hodgdon H110	Speer	CCI 350	25.5	1533	27.5	1645
Vihtavuori N110	Speer	CCI 300	21.0	1434	23.0	1607
Accurate No. 9	Speer	CCI 300	21.0	1504	23.0	1587
Ramshot Enforcer	Speer	CCI 350	22.0	1491	24.0	1577
Alliant 2400	Speer	CCI 300	21.5	1428	23.5	1566
Hodgdon Lil' Gun	Speer	CCI 350	26.0	1509	28.0	1566
Alliant Power Pistol	Speer	CCI 300	12.5	1324	14.5	1504
Alliant Unique	Speer	CCI 300	10.5	1212	12.5	1392
Hodgdon H. Universal	Speer	CCI 300	9.0	1132	11.0	1320

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load