



## 44 Remington Magnum

<b>.430"</b>	<b>44</b>
<b>Weight (grains)</b>	<b>LSWC</b>
<b>Ballistic Coefficient</b>	240
<b>Sectional Density</b>	0.141
<b>COAL Tested</b>	0.185
<b>Speer Part No.</b>	1.605"
	4661

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Hodgdon HS-6	Speer	CCI 300	8.5	822	<b>9.5</b>	947
IMR SR 4756	Speer	CCI 300	6.5	751	<b>7.5</b>	923
IMR SR 7625	Speer	CCI 300	6.0	834	<b>7.0</b>	912
Alliant Red Dot	Speer	CCI 300	6.0	871	<b>6.5</b>	905
Alliant Green Dot	Speer	CCI 300	6.0	804	<b>7.0</b>	901
Alliant Unique	Speer	CCI 300	6.5	720	<b>7.0</b>	899
Alliant Bullseye	Speer	CCI 300	5.5	828	<b>6.0</b>	894
Hodgdon Hi-Skor 700-X	Speer	CCI 300	5.5	836	<b>6.0</b>	871
Winchester 231	Speer	CCI 300	6.0	808	<b>6.5</b>	867

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*