



44 Smith & Wesson Special

.429"	44
Weight (grains)	GDHP
Ballistic Coefficient	200
Sectional Density	0.145
COAL Tested	0.155
Speer Part No.	1.490"
	4427

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Power Pistol	Remington	CCI 300	7.6	872	8.6	976
Vihtavuori N350	Remington	CCI 300	8.0	823	8.8	952
Hodgdon H. Universal	Remington	CCI 300	7.0	842	7.6	950
Accurate No. 5	Remington	CCI 300	8.8	805	9.9	935
Hodgdon Hi-Skor 700-X	Remington	CCI 300	5.3	800	6.1	902
Hodgdon TITEGROUP	Remington	CCI 300	5.3	795	6.1	902
Winchester 231	Remington	CCI 300	6.0	730	6.9	886
Alliant Bullseye	Remington	CCI 300	5.1	766	5.9	884
Alliant Red Dot	Remington	CCI 300	5.4	801	5.9	868
Alliant Unique	Remington	CCI 300	7.0	788	7.8	855
Accurate No. 2 Improved	Remington	CCI 300	DNR	—	5.9	828
Alliant American Select	Remington	CCI 300	DNR	—	5.7	821

DNR — do not reduce

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load