



454 Casull

.451" (260 gr) .452" (250 gr)	45 DCHP	45 JHP
Weight (grains)	250	260
Ballistic Coefficient	0.165	0.183
Sectional Density	0.175	0.183
COAL Tested	1.670"	1.670"
Speer Part No.	4484	4481

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Power Pro 300-MP	Federal	Federal 205	29.0	1446	31.1	1572
Alliant 2400	Starline	CCI 400	24.0	1422	26.0	1531
Ramshot Enforcer	Federal	Federal 205	24.1	1328	27.2	1510
Vihtavuori N110	Starline	CCI 400	23.0	1381	25.0	1499
Alliant Power Pistol	Federal	Federal 205	13.4	1277	15.0	1402
IMR 4227	Starline	CCI 400	27.0	1248	29.0 C	1399
Accurate No. 9	Starline	CCI 400	23.0	1323	25.0	1375
Accurate 5744	Starline	CCI 400	26.0	1225	28.0	1341
Alliant BE-86	Federal	Federal 205	12.4	1259	13.9	1339
Ramshot True Blue	Starline	CCI 400	14.0	1164	16.0	1325
Vihtavuori N350	Starline	CCI 400	13.0	1129	15.0	1277
Hodgdon CFE Pistol	Federal	Federal 205	11.9	1188	13.2	1276

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load