



454 Casull

.452"	45
Weight (grains)	DCHP
Ballistic Coefficient	300
Sectional Density	0.233
COAL Tested	0.210
Speer Part No.	1.750"
	3974

FULL POWER LOADS

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Hodgdon H110	Winchester	CCI 400	29.5	1506	31.5 C	1630
Winchester 296	Winchester	CCI 400	29.0	1475	31.0 C	1587
Vihtavuori N110	Winchester	CCI 400	25.5	1446	27.5	1549
Accurate No. 9	Winchester	CCI 400	24.5	1403	26.5	1535
Alliant 2400	Winchester	CCI 400	25.0	1379	27.0	1479
IMR 4227	Winchester	CCI 400	28.0	1320	30.0 C	1426

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load