



## 45 Automatic

<b>.452"</b>	<b>45</b>
<b>Weight (grains)</b>	<b>LRN</b>
<b>Ballistic Coefficient</b>	230
<b>Sectional Density</b>	0.160
<b>COAL Tested</b>	0.161
<b>Speer Part No.</b>	1.240"
	4691

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Hodgdon CFE Pistol	Federal	Federal 150	5.6	809	<b>7.2</b>	989
Winchester AutoComp	Federal	Federal 150	5.6	795	<b>7.3</b>	988
Alliant BE 86	Federal	Federal 150	5.8	850	<b>7.2</b>	986
Alliant Herco	Federal	Federal 150	5.9	884	<b>6.4</b>	931
Alliant Sport Pistol	Federal	Federal 150	4.4	777	<b>5.6</b>	919
Alliant Green Dot	Federal	Federal 150	4.8	847	<b>5.3</b>	908
Alliant Red Dot	Federal	Federal 150	4.7	856	<b>5.1</b>	899
Alliant Unique	Federal	Federal 150	5.3	837	<b>5.8</b>	895
Hodgdon Hi-Skor 700-X	Federal	Federal 150	4.3	839	<b>4.7</b>	890
Hodgdon H. Universal	Federal	Federal 150	5.2	818	<b>5.5</b>	867
Winchester 231	Federal	Federal 150	5.1	794	<b>5.6</b>	853
IMR SR 4756	Federal	Federal 150	6.0	739	<b>6.5</b>	816

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*