



45 Colt

.451"	45
Weight (grains)	GDHP
Ballistic Coefficient	200
Sectional Density	0.138
COAL Tested	0.140
Speer Part No.	1.555"
	4478

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Hodgdon HS-6	Winchester	CCI 350	11.0	945	12.5	1081
Alliant Unique	Winchester	CCI 300	8.8	940	9.8	1048
Alliant Herco	Winchester	CCI 300	9.0	928	10.0	1032
IMR SR 7625	Winchester	CCI 300	7.7	880	8.7	1002
Alliant Bullseye	Winchester	CCI 300	7.4	920	7.9	994
Alliant Green Dot	Winchester	CCI 300	7.8	868	8.8	991
Hodgdon H. Universal	Winchester	CCI 300	8.4	892	9.2	985
Alliant Red Dot	Winchester	CCI 300	7.1	911	7.6	981
Hodgdon Hi-Skor 700-X	Winchester	CCI 300	6.1	852	7.1	921
Alliant Power Pistol	Winchester	CCI 300	8.6	829	9.2	885
Hodgdon TITEGROUP	Winchester	CCI 300	6.2	788	6.8	865

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load