



45 Colt

.452"	45
Weight (grains)	LSWC
Ballistic Coefficient	250
Sectional Density	0.117
COAL Tested	0.175
Speer Part No.	1.600"
	4684

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Blue Dot	Winchester	CCI 300	11.9	912	12.9	1028
Vihtavuori 3N37	Winchester	CCI 300	10.5	889	11.5	1012
Alliant 2400	Winchester	CCI 300	13.4	838	15.4	972
Hodgdon HS-6	Winchester	CCI 350	11.0	917	12.0	945
Hodgdon H. Universal	Winchester	CCI 300	8.3	826	9.2	942
Alliant Unique	Winchester	CCI 300	8.6	891	9.5	941
Accurate No. 5	Winchester	CCI 300	10.6	840	11.6	927
IMR 4227	Winchester	CCI 300	17.0	775	19.0	904
Alliant Bullseye	Winchester	CCI 300	6.3	810	7.0	879
Winchester 231	Winchester	CCI 300	7.2	780	8.0	852

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load