



45 G.A.P.

.451"	45
Weight (grains)	185
Ballistic Coefficient	0.109
Sectional Density	0.130
COAL Tested	1.070"
Speer Part No.	4470

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Hodgdon H. Universal	Speer	CCI 500	6.3	938	6.8	1044
Alliant Bullseye	Speer	CCI 500	5.5	950	6.1	1037
Vihtavuori 3N37	Speer	CCI 500	7.7	881	8.4	1018
Alliant Unique	Speer	CCI 500	7.1	984	7.7	1009
Ramshot True Blue	Speer	CCI 500	7.4	908	8.2	1005
Winchester 231	Speer	CCI 500	5.5	892	6.2	1000
Accurate No. 5	Speer	CCI 500	8.1	922	8.8	999
Hodgdon TITEGROUP	Speer	CCI 500	5.1	934	5.6	994
Alliant Power Pistol	Speer	CCI 500	7.2	927	7.8	993
Accurate No. 2 Improved	Speer	CCI 500	4.6	807	5.2	897

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load