



380 Automatic

.355"	380
Weight (grains)	90
Ballistic Coefficient	0.101
Sectional Density	0.102
COAL Tested	0.970"
Speer Part No.	3992

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Accurate No. 2 Improved	Winchester	CCI 500	3.5	982	3.9	1056
Accurate No. 7	Winchester	CCI 500	6.3	941	7.0 C	1050
Vihtavuori N320	Winchester	CCI 500	3.1	953	3.4	1044
Alliant Unique	Winchester	CCI 500	4.1	877	4.6 C	1034
Winchester 231	Winchester	CCI 500	3.6	978	4.0	1031
Alliant Power Pistol	Winchester	CCI 500	4.4	944	4.8 C	1020
Hodgdon H. Universal	Winchester	CCI 500	3.8	821	4.3	994
Hodgdon Hi-Skor 700-X	Winchester	CCI 500	3.2	812	3.6	988
Accurate No. 5	Winchester	CCI 500	4.8	845	5.4	984
Alliant Bullseye	Winchester	CCI 500	3.0	885	3.4	981
Hodgdon TITEGROUP	Winchester	CCI 500	2.8	885	3.2	976
Winchester WSL	Winchester	CCI 500	3.2	825	3.6	972
Alliant BE 86	Federal	Federal 100	3.2	804	3.9	963
Alliant American Select	Winchester	CCI 500	2.8	841	3.3	955
Winchester AutoComp	Federal	Federal 100	3.5	863	3.9	954
Hodgdon CFE Pistol	Federal	Federal 100	3.4	861	3.8	948
Alliant Sport Pistol	Federal	Federal 100	2.4	773	2.9	914

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load