



9mm Luger

.356"	9mm
Weight (grains)	125
Ballistic Coefficient	0.155
Sectional Density	0.142
COAL Tested	1.130"
Speer Part No.	4602

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Winchester WAP	Speer	CCI 500	4.2	921	4.6	1012
Alliant Unique	Speer	CCI 500	4.1	911	4.5	1007
Alliant Red Dot	Speer	CCI 500	3.3	888	3.6	1004
Hodgdon HP38	Speer	CCI 500	3.9	917	4.2	995
Hodgdon HS-6	Speer	CCI 500	5.1	913	5.5	993
Hodgdon H. Universal	Speer	CCI 500	3.9	899	4.3	991
Winchester 231	Speer	CCI 500	3.8	911	4.1	982
Hodgdon Hi-Skor 700-X	Speer	CCI 500	3.2	920	3.4	977
Alliant Bullseye	Speer	CCI 500	3.5	929	3.8	962

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load