



22-250 Remington

.224"	22
Weight (grains)	Spitzer SP
Ballistic Coefficient	50
Sectional Density	0.207
COAL Tested	0.142
Speer Part No.	2.350"
	1029

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
IMR 8208 XBR	Federal	Federal 210	31.8	3635	35.3	3875
Alliant AR-Comp	Federal	Federal 210	31.8	3570	35.2	3862
Alliant Reloder 10X	Remington	CCI 200	30.0	3491	34.0	3837
Accurate 2460	Remington	CCI 250	33.0	3355	37.0	3804
Hodgdon Varget	Remington	CCI 200	32.5	3283	36.5	3796
Alliant Reloder 15	Remington	CCI 200	34.0	3209	38.0	3736
Vihtavuori N135	Remington	CCI 200	32.0	3231	36.0	3693
Hodgdon H380	Remington	CCI 250	38.0	3229	42.0 C	3693
Alliant Power Pro 1200-R	Federal	Federal 210	26.6	3353	29.4	3686
Accurate 2230	Remington	CCI 250	31.0	3188	35.0	3685
Winchester 760	Remington	CCI 250	37.0	3218	41.0	3636
IMR 4064	Remington	CCI 200	33.0	3136	37.0	3625
Hodgdon H414	Remington	CCI 250	37.0	3081	41.0	3604
IMR 4320	Remington	CCI 200	34.0	3117	38.0	3603
Winchester 748	Remington	CCI 250	34.0	3079	38.0	3601
IMR 4895	Remington	CCI 200	31.5	3116	35.5	3561
Hodgdon BL-C(2)	Remington	CCI 250	33.0	3149	37.0	3558
IMR SR 4759 (reduced load)	Remington	CCI 200	10.0	1650	12.0	1982

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load