



22-250 Remington

.224"	22 TNT Green®
Weight (grains)	43
Ballistic Coefficient	0.150
Sectional Density	0.122
COAL Tested	2.320"
Speer Part No.	1022

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Vihtavuori N540	Federal	Federal 210	38.5	3976	40.5	4175
IMR 4895	Federal	Federal 210	38.0	3925	40.0 C	4154
Alliant Reloder 15	Federal	Federal 210	36.5	3909	38.5	4125
Hodgdon Varget	Federal	Federal 210	38.0	3951	40.0 C	4121
Ramshot TAC	Federal	Federal 210	33.0	3809	37.0	4107
Alliant Reloder 10X	Federal	Federal 210	32.0	3919	34.0	4077

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load