



## 220 Swift

<b>.224"</b>	<b>22</b>
<b>Weight (grains)</b>	<b>Spitzer SP</b>
<b>Ballistic Coefficient</b>	45
<b>Sectional Density</b>	0.143
<b>COAL Tested</b>	0.128
<b>Speer Part No.</b>	2.650"
	1023

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Power Pro 2000-MR	Hornady	CCI 200	37.4	3717	41.6	4069
Alliant Reloder 17	Hornady	CCI 200	40.0	3699	43.3	4060
Alliant Power Pro Varmint	Hornady	CCI 200	34.9	3698	38.7	4024
Alliant AR-Comp	Hornady	CCI 200	33.5	3709	37.2	4006
IMR 4451	Hornady	CCI 200	40.5	3615	45.0 C	3995
Alliant Reloder 16	Hornady	CCI 200	40.5	3691	43.5 C	3944
Alliant Reloder 15	Winchester	CCI 200	37.5	3471	41.5	3923
Vihtavuori N160	Winchester	CCI 200	42.0	3421	46.0 C	3819
Hodgdon H380	Winchester	CCI 250	40.5	3482	44.5 C	3806
Vihtavuori N140	Winchester	CCI 200	35.5	3360	39.5	3740
Winchester 760	Winchester	CCI 250	38.5	2282	42.5	3712
Accurate 4350	Winchester	CCI 200	41.0	3273	45.0 C	3700
Alliant Reloder 19	Winchester	CCI 200	42.0	3281	46.0 C	3658
IMR 3031	Winchester	CCI 200	33.5	3275	37.5	3649
IMR 4064	Winchester	CCI 200	33.5	3229	37.5	3582
IMR 4350	Winchester	CCI 200	40.5	3019	44.5 C	3413
IMR SR 4759 (reduced load)	Winchester	CCI 200	10.5	1631	12.5	1930

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*