



220 Swift

.224"	22 TNT® HP	22 Spitzer SP
Weight (grains)	55	55
Ballistic Coefficient	0.233	0.212
Sectional Density	0.157	0.157
COAL Tested	2.680"	2.650"
Speer Part No.	1032	1047

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 16	Hornady	CCI 200	39.3	3484	43.5 C	3846
Alliant Reloder 17	Hornady	CCI 200	37.7	3418	41.6	3793
Alliant Power Pro 4000-MR	Hornady	CCI 200	39.6	3372	43.8	3769
Alliant Power Pro 2000-MR	Hornady	CCI 200	35.6	3501	39.4	3730
Vihtavuori N160	Winchester	CCI 200	42.0	3340	46.0 C	3730
Accurate 4350	Winchester	CCI 200	41.0	3280	45.0 C	3708
IMR 4451	Hornady	CCI 200	38.1	3342	42.3	3692
Alliant AR-Comp	Hornady	CCI 200	32.3	3442	35.8	3670
Alliant Reloder 19	Winchester	CCI 200	42.0	3174	46.0 C	3637
Vihtavuori N140	Winchester	CCI 200	35.0	3256	39.0	3624
Hodgdon H380	Winchester	CCI 250	39.0	3304	43.0	3610
Alliant Reloder 15	Winchester	CCI 200	35.0	3221	39.0	3585
IMR 4320	Winchester	CCI 200	35.0	3225	39.0	3536
IMR 4350	Winchester	CCI 200	39.0	3116	43.0	3523
Hodgdon H4831SC	Winchester	CCI 200	41.0	3053	45.0 C	3516
Accurate 2700	Winchester	CCI 250	37.0	3203	41.0	3500
Winchester 760	Winchester	CCI 250	36.5	3116	40.5	3468
IMR 3031	Winchester	CCI 200	32.0	3149	36.0	3442
IMR SR 4759 (reduced load)	Winchester	CCI 200	11.5	1707	13.5	1990

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load