



speer
bullets

222 Remington Magnum

.224"	22 TNT® HP	22 Spitz SP
Weight (grains)	55	55
Ballistic Coefficient	0.233	0.212
Sectional Density	0.157	0.157
COAL Tested	2.250"	2.250"
Speer Part No.	1032	1047

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Hodgdon H335	Remington	CCI 450	25.5	3090	27.5	3350
IMR 4320	Remington	CCI 400	26.0	3091	28.0	3318
Hodgdon BL-C(2)	Remington	CCI 450	24.5	3044	26.5	3302
IMR 4064	Remington	CCI 400	25.5	3083	27.5	3301
IMR 3031	Remington	CCI 400	24.0	3059	26.0	3297
IMR 4895	Remington	CCI 400	24.5	3046	26.5	3282
Hodgdon H414	Remington	CCI 450	29.0	2988	31.0	3230
IMR SR 4759 (reduced load)	Remington	CCI 400	9.0	1694	11.0	2068

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load