



222 Remington Magnum

.224"	22
	Semi Spitz SP
Weight (grains)	70
Ballistic Coefficient	0.219
Sectional Density	0.199
COAL Tested	2.260"
Speer Part No.	1053

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
IMR 4064	Remington	CCI 400	24.5	2825	26.5	3049
IMR 4320	Remington	CCI 400	24.5	2781	26.5	2988
IMR 4895	Remington	CCI 400	23.0	2727	25.0	2943
Hodgdon H335	Remington	CCI 450	23.0	2685	25.0	2943
IMR 3031	Remington	CCI 400	22.0	2659	24.0	2885
Hodgdon H414	Remington	CCI 450	26.0	2655	28.0	2878
Hodgdon H380	Remington	CCI 450	27.0	2621	29.0	2855
IMR SR 4759 (reduced load)	Remington	CCI 400	10.0	1615	12.0	1926

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load