



223 Remington

0.224	22 TNT HP	22 Spitzer SP
Weight (grains)	55	55
Ballistic Coefficient	0.233	0.212
Sectional Density	0.157	0.157
COAL Tested	2.235"	2.175"
Speer Part No.	1032	1047

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Winchester 748	IMI	CCI 450	26.0	3008	28.0 C	3369
IMR 8208 XBR	Federal	Federal 205	23.7	3045	26.0	3305
Hodgdon CFE 223	Federal	Federal 205	24.6	3004	27.2	3291
Accurate 2230	IMI	CCI 400	24.0	3062	26.0	3286
IMR 3031	IMI	CCI 400	24.0	3019	26.0 C	3276
Alliant Power Pro Varmint	Federal	Federal 205	23.7	3014	25.9	3270
Hodgdon Varget	IMI	CCI 400	25.0	3012	27.0	3268
Hodgdon H4895	IMI	CCI 400	23.5	2949	25.5 C	3246
Alliant AR-Comp	Federal	Federal 205	22.2	3021	24.6 C	3245
Accurate 2520	IMI	CCI 450	25.0	3066	27.0 C	3238
Alliant Power Pro 1200-R	Federal	Federal 205	21.0	2972	23.1	3210
Alliant Reloder 10X	IMI	CCI 400	21.0	2976	23.0	3209
Hodgdon H322	IMI	CCI 400	22.5	2860	24.5	3208
IMR 4064	IMI	CCI 400	24.5	2881	26.5	3193
Hodgdon BL-C(2)	IMI	CCI 450	25.0	2907	27.0	3187
Hodgdon H335	IMI	CCI 450	24.0	2842	26.0	3140
Vihtavuori N133	IMI	CCI 400	21.5	2811	23.5	3139
Accurate 2015	IMI	CCI 400	21.5	2788	23.5	3071
Hodgdon H4198	IMI	CCI 400	19.0	2726	21.0	3021
Accurate 5744 (reduced load)	IMI	CCI 400	11.0	1892	12.0	2033

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load