



225 Winchester

.224"	22
Weight (grains)	Spire SP
Ballistic Coefficient	40
Sectional Density	0.144
COAL Tested	0.114
Speer Part No.	2.370"
	1017

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
IMR 3031	Winchester	CCI 200	28.5	3391	32.5	3815
IMR 4064	Winchester	CCI 200	30.5	3344	34.5	3791
Hodgdon H380	Winchester	CCI 250	34.0	3351	38.0 C	3717
Winchester 748	Winchester	CCI 250	31.0	3310	35.0	3711
Hodgdon H322	Winchester	CCI 200	27.5	3214	31.5	3683
Winchester 760	Winchester	CCI 250	34.0	3331	38.0 C	3682
IMR 4350	Winchester	CCI 200	33.0	3273	37.0 C	3614
Hodgdon H335	Winchester	CCI 250	27.5	3078	31.5	3496
IMR SR 4759 (reduced load)	Winchester	CCI 200	8.0	1560	10.0	1967

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load