



## 225 Winchester

.224"	22 Spitzer SP	22 TNT® HP
Weight (grains)	50	50
Ballistic Coefficient	0.207	0.228
Sectional Density	0.142	0.142
COAL Tested	2.460"	2.480"
Speer Part No.	1029	1030

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
IMR 4064	Winchester	CCI 200	29.5	3202	33.5	3641
Winchester 748	Winchester	CCI 250	30.5	3224	34.5	3615
Winchester 760	Winchester	CCI 250	33.0	3183	37.0	3557
Hodgdon H414	Winchester	CCI 250	33.0	3159	37.0	3545
IMR 4350	Winchester	CCI 200	32.5	3150	36.5 C	3526
Hodgdon H322	Winchester	CCI 200	26.5	3138	30.5	3507
IMR 3031	Winchester	CCI 200	27.5	3030	31.5	3446
Hodgdon H380	Winchester	CCI 250	32.0	3093	36.0	3440
IMR SR 4759 (reduced load)	Winchester	CCI 200	9.5	1679	11.5	2027

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*