



5.56x45mm NATO

.224"	22 GD
Weight (grains)	75
Ballistic Coefficient	0.411
Sectional Density	0.214
COAL Tested	2.260"
Speer Part No.	22475GDB

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Power Pro 2000-MR	Federal	CCI 41	24.4	2541	27.1 C	2849
Alliant Power Pro Varmint	Federal	CCI 41	22.0	2485	24.5	2744
Alliant Reloder 15	Federal	CCI 41	22.3	2456	24.8 C	2721
IMR 4895	Federal	CCI 41	22.1	2498	24.4 C	2705
Ramshot X-Terminator	Federal	CCI 41	21.2	2484	23.6	2701
Accurate 2460	Federal	CCI 41	22.1	2515	24.4	2701
Hodgdon Varget	Federal	CCI 41	22.3	2562	23.6 C	2667
Vihtavuori N540	Federal	CCI 41	22.0	2372	24.5	2658
Alliant AR-Comp	Federal	CCI 41	20.3	2437	22.6 C	2655
Hodgdon H335	Federal	CCI 41	21.1	2423	23.3	2634

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load