



243 Winchester Super Short Magnum

.243"	6mm TNT® HP	6mm HP
Weight (grains)	70	75
Ballistic Coefficient	0.279	0.192
Sectional Density	0.169	0.181
COAL Tested	2.250"	2.185"
Speer Part No.	1206	1205

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Hodgdon H414	Winchester	Federal® 215	45.0	3417	47.0	3547
Winchester 760	Winchester	Federal 215	45.5	3409	47.5	3531
Vihtavuori N540	Winchester	Federal 210	40.0	3367	42.0	3484
IMR 4350	Winchester	Federal 210	44.5	3358	46.5	3483
Alliant Reloder® 15	Winchester	Federal 210	39.0	3350	41.0	3478
Alliant Reloder 19	Winchester	Federal 210	47.5	3337	49.5 C	3464
IMR 4895	Winchester	Federal 210	38.5	3333	40.5	3461
Hodgdon Varget	Winchester	Federal 210	39.0	3347	41.0	3456
Ramshot Big Game	Winchester	Federal 215	43.0	3339	45.0	3454
Accurate 4350	Winchester	Federal 210	45.0	3262	47.0 C	3404
Accurate 4064	Winchester	Federal 210	37.5	3214	39.5	3341

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load