



264 Winchester Magnum

.264"	6.5mm
Weight (grains)	Spitzer SP Hot-Cor®
Ballistic Coefficient	140
Sectional Density	0.498
COAL Tested	0.287
Speer Part No.	3.250"
	1441

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Hodgdon US 869	Hornady	CCI 250	67.6	2795	74.4	3050
Alliant Reloder 33	Hornady	CCI 250	61.7	2739	68.2	2989
Alliant Reloder 50	Hornady	CCI 250	62.8	2773	69.3	2986
Hodgdon Retumbo	Hornady	CCI 250	56.4	2735	62.7	2966
Alliant Reloder 25	Hornady	CCI 250	54.2	2709	60.1	2932
Ramshot Magnum	Hornady	CCI 250	56.8	2708	62.5	2929
IMR 7828	Hornady	CCI 250	52.4	2678	58.2	2916
Alliant Reloder 26	Hornady	CCI 250	52.5	2699	58.1	2912
Vihtavouri N560	Hornady	CCI 250	51.6	2680	57.3	2911
Alliant Reloder 22	Hornady	CCI 250	50.6	2695	55.8	2890
IMR 7977	Hornady	CCI 250	55.9	2628	62.1	2890
Alliant Reloder 23	Hornady	CCI 250	52.4	2698	56.9	2877
Alliant Reloder 19	Hornady	CCI 250	49.2	2655	54.6	2863
Alliant Power Pro 4000-MR	Hornady	CCI 250	49.6	2631	55.0	2857
Accurate 3100	Winchester	CCI 250	51.0	2704	55.0	2854

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load