



6mm Remington

.243"	6mm
	TNT® HP
Weight (grains)	70
Ballistic Coefficient	0.279
Sectional Density	0.169
COAL Tested	2.775"
Speer Part No.	1206

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 17	Federal	Federal 210	43.9	3252	48.7 C	3644
Hodgdon H4350	Remington	CCI 200	47.0	3198	51.0 C	3593
Accurate 4350	Remington	CCI 200	48.0	3106	52.0 C	3531
Alliant Reloder 16	Federal	Federal 210	44.0	3313	47.0 C	3525
Alliant Power Pro 4000-MR	Federal	Federal 210	45.1	3269	49.0 C	3522
IMR 4451	Federal	Federal 210	44.0	3215	48.2 C	3516
Alliant Reloder 19	Remington	CCI 200	49.0	3262	53.0 C	3507
Alliant Reloder 22	Remington	CCI 200	50.0	3287	54.0 C	3497
IMR 4831	Remington	CCI 200	48.0	3171	52.0 C	3485
Hodgdon H380	Remington	CCI 250	42.0	3132	47.0	3442
IMR 4064	Remington	CCI 200	40.0	3119	44.0	3427
Winchester 760	Remington	CCI 250	44.0	3078	48.0	3420
IMR 4350	Remington	CCI 200	45.0	3040	49.0	3416
IMR 4895	Remington	CCI 200	38.0	3111	42.0	3381
Hodgdon H414	Remington	CCI 250	44.0	3100	48.0	3370
Vihtavuori N140	Remington	CCI 200	39.0	3023	43.0	3322
Hodgdon H4831	Remington	CCI 250	48.0	3104	52.0 C	3302

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load