



6mm Remington

.243"	6mm
Weight (grains)	HP
Ballistic Coefficient	75
Sectional Density	0.192
COAL Tested	0.181
Speer Part No.	2.775"
	1205

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Power Pro 4000-MR	Federal	Federal 210	45.0	3198	49.8 C	3521
Hodgdon H4350	Remington	CCI 200	46.0	3157	50.0 C	3515
Alliant Reloder 17	Federal	Federal 210	43.3	3198	48.1	3504
Accurate 4350	Remington	CCI 200	47.0	3083	51.0 C	3495
Alliant Reloder 16	Federal	Federal 210	42.7	3179	47.2 C	3494
Alliant Reloder 22	Remington	CCI 200	49.0	3262	53.0 C	3474
Accurate 2700	Remington	CCI 250	43.0	3147	47.0	3458
IMR 4451	Federal	Federal 210	42.9	3184	47.4 C	3446
Alliant Reloder 19	Remington	CCI 200	48.0	3165	52.0 C	3440
IMR 4350	Remington	CCI 200	44.0	3064	48.0 C	3367
Winchester 760	Remington	CCI 250	43.0	3018	47.0	3318
Hodgdon H4831	Remington	CCI 250	47.0	3045	51.0 C	3310
Hodgdon H380	Remington	CCI 250	42.0	3012	46.0	3310
IMR 4831	Remington	CCI 200	45.0	3001	49.0 C	3298
Vihtavuori N140	Remington	CCI 200	39.0	2999	43.0	3293
IMR 4064	Remington	CCI 200	38.5	3010	42.5	3272
IMR 4895	Remington	CCI 200	37.0	2969	41.0	3248
Hodgdon H414	Remington	CCI 250	42.0	2959	46.0	3216

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load