



## 25-06 Remington

.257"	25 Spitzer SP Hot- Cor®	25 HP	25 Spitzer BTSP
Weight (grains)	100	100	100
Ballistic Coefficient	0.334	0.263	0.393
Sectional Density	0.216	0.216	0.216
COAL Tested	3.095"	3.095"	3.095"
Speer Part No.	1405	1407	1408

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 23	Federal	Federal 210	50.5	3000	55.0	3323
Alliant Reloder 17	Federal	Federal 210	46.5	2956	51.3	3301
IMR 4350	Winchester	CCI 200	49.0	3067	53.0	3298
IMR 4831	Winchester	CCI 200	52.0	2997	56.0	3287
Alliant Reloder 22	Winchester	CCI 200	54.0	2945	58.0	3248
Alliant Power Pro 4000-MR	Federal	Federal 210	48.0	2947	52.8	3235
Alliant Reloder 19	Winchester	CCI 200	53.0	2903	57.0	3226
Alliant Reloder 25	Winchester	CCI 200	57.0	3123	59.0 C	3224
IMR 7828	Winchester	CCI 200	56.0	2892	60.0 C	3222
Hodgdon H4831SC	Winchester	CCI 200	51.0	2999	55.0	3215
Hodgdon H1000	Winchester	CCI 200	57.0	2933	61.0 C	3151
Vihtavuori N160	Winchester	CCI 200	49.0	2828	53.0	3129
Accurate 3100	Winchester	CCI 200	52.0	2845	56.0	3120
Hodgdon H414	Winchester	CCI 250	46.0	2783	50.0	3111
Hodgdon H870	Winchester	CCI 250	61.0	2887	65.0 C	3106
IMR SR 4759 (reduced load)	Winchester	CCI 200	15.0	1524	19.0	1892

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*