



250 Savage

.257"

25
Spitzer BTSP

Weight (grains)	120
Ballistic Coefficient	0.480
Sectional Density	0.260
COAL Tested	2.450"
Speer Part No.	1410

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 17	Hornady	CCI 200	33.5	2452	35.9	2619
Alliant Power Pro Varmint	Hornady	CCI 200	29.0	2416	32.0	2597
Hodgdon H414	Winchester	CCI 250	32.0	2290	36.0	2511
Winchester 760	Winchester	CCI 250	32.0	2289	36.0	2507
Alliant Reloder 19	Winchester	CCI 200	34.0	2200	38.0	2497
IMR 4166	Hornady	CCI 200	27.0	2333	30.3	2488
IMR 4831	Winchester	CCI 200	33.0	2116	37.0	2421
Accurate 3100	Winchester	CCI 200	33.0	2163	37.0 C	2411
Alliant Reloder 15	Winchester	CCI 200	27.0	2123	31.0	2397
IMR 4320	Winchester	CCI 200	27.0	2084	31.0	2371
Hodgdon H380	Winchester	CCI 250	29.0	2159	33.0	2370
Hodgdon H4350	Winchester	CCI 200	31.0	2059	35.0 C	2354
IMR 4350	Winchester	CCI 200	30.0	2062	34.0	2344
IMR 4198 (reduced load)	Winchester	CCI 200	18.0	1644	20.0	1858

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load