



## 250 Savage

.257"	25 Spitzer SP Hot- Cor®	25 TNT® HP
Weight (grains)	87	87
Ballistic Coefficient	0.300	0.337
Sectional Density	0.188	0.188
COAL Tested	2.465"	2.500"
Speer Part No.	1241	1246

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Hodgdon CFE 223	Hornady	CCI 200	37.5	3046	39.7	3207
Alliant Power Pro 2000-MR	Hornady	CCI 200	36.5	2937	40.1	3164
Alliant Power Pro Varmint	Hornady	CCI 200	34.0	2947	37.0	3148
Hodgdon H380	Winchester	CCI 250	38.0	2821	42.0 C	3097
Hodgdon Benchmark	Hornady	CCI 200	31.5	2929	33.9	3059
IMR 8208 XBR	Hornady	CCI 200	32.5	2891	34.9	3051
Alliant AR-Comp	Hornady	CCI 200	30.5	2868	33.8	3048
Hodgdon H414	Winchester	CCI 250	37.0	2749	41.0 C	3005
Winchester 760	Winchester	CCI 250	37.0	2733	41.0 C	2994
Alliant Reloder 15	Winchester	CCI 200	33.0	2642	37.0	2982
IMR 4350	Winchester	CCI 200	37.0	2589	41.0 C	2963
Accurate 2700	Winchester	CCI 250	37.0	2646	41.0	2901
IMR 4831	Winchester	CCI 200	38.0	2507	42.0 C	2866
IMR 4064	Winchester	CCI 200	31.0	2578	35.0	2849
Winchester 748	Winchester	CCI 250	31.0	2486	35.0	2793
Accurate 3100	Winchester	CCI 200	37.0	2451	41.0 C	2788
Hodgdon BL-C(2)	Winchester	CCI 250	31.0	2476	35.0	2767
SR 4759 (reduced load)	Winchester	CCI 200	12.5	1622	14.5	1928

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load