



257 Roberts +P

.257"	25
Weight (grains)	Spitzer BTSP
Ballistic Coefficient	120
Sectional Density	0.480
COAL Tested	0.260
Speer Part No.	2.770"
	1410

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Power Pro 4000-MR	Federal	Federal 210	40.2	2589	44.7	2858
Alliant Reloder 23	Federal	Federal 210	41.2	2608	45.8 C	2852
Alliant Reloder 16	Federal	Federal 210	38.6	2590	42.8	2836
Alliant Reloder 17	Federal	Federal 210	38.5	2586	42.5	2826
Ramshot Hunter	Federal	Federal 210	39.8	2631	43.6	2817
IMR 4831	Winchester	CCI 200	41.0	2552	45.0	2793
Winchester 760	Winchester	CCI 250	39.0	2496	43.0	2770
Hodgdon H414	Winchester	CCI 250	39.0	2507	43.0	2767
IMR 4350	Winchester	CCI 200	39.0	2512	43.0	2758
Alliant Reloder 19	Winchester	CCI 200	39.0	2476	43.0	2709
IMR 4064	Winchester	CCI 200	34.0	2423	38.0	2705
Alliant Reloder 22	Winchester	CCI 200	39.0	2399	43.0	2635
IMR 7828	Winchester	CCI 200	40.0	2304	44.0	2583
IMR 4320	Winchester	CCI 200	32.0	2316	36.0	2545
Alliant Reloder 15	Winchester	CCI 200	30.0	2322	34.0	2541
IMR 4895	Winchester	CCI 200	30.0	2249	34.0	2527
Accurate XMR 3100	Winchester	CCI 200	38.0	2301	42.0	2507
Hodgdon H380	Winchester	CCI 250	33.0	2275	37.0	2482
IMR SR 4759 (reduced load)	Winchester	CCI 200	17.0	1776	19.0	2003

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load