



257 Weatherby Magnum

.257"	25 Spitzer SP Hot- Cor®	25 TNT® HP
Weight (grains)	87	87
Ballistic Coefficient	0.300	0.337
Sectional Density	0.188	0.188
COAL Tested	3.150"	3.170"
Speer Part No.	1241	1246

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Ramshot Magnum	Federal	CCI 250	74.0	3570	78.0	3731
Hodgdon Retumbo	Federal	CCI 250	74.0	3462	78.0 C	3672
Alliant Reloder 25	Federal	CCI 250	69.0	3427	73.0 C	3670
Alliant Reloder 22	Federal	CCI 250	67.0	3429	71.0	3661
Vihtavuori N560	Federal	CCI 250	68.0	3507	70.0	3651
Alliant Reloder 19	Federal	CCI 250	64.0	3372	68.0	3637
IMR 7828	Federal	CCI 250	67.0	3334	71.0	3604
IMR 4831	Federal	CCI 250	63.0	3433	65.0	3564
Accurate MagPro	Federal	CCI 250	68.0	3400	70.0	3504

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load