



270 Weatherby Magnum

.277"	270
	HP
Weight (grains)	100
Ballistic Coefficient	0.201
Sectional Density	0.186
COAL Tested	3.250"
Speer Part No.	1447

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 26	Federal	Federal 215	68.5	3263	75.9	3680
Alliant Reloder 22	Federal	Federal 215	72.0	3423	76.0 C	3627
Alliant Power Pro 4000-MR	Federal	Federal 215	63.6	3296	70.4	3619
Accurate Magpro	Federal	Federal 215	76.0	3451	80.0 C	3618
Alliant Reloder 23	Federal	Federal 215	65.9	3266	72.9	3595
IMR 4831	Federal	Federal 215	67.0	3360	71.0	3575
Alliant Reloder 19	Federal	Federal 215	69.0	3359	73.0	3570
Ramshot Magnum	Federal	Federal 215	77.0	3386	81.0 C	3557
Hodgdon H4831SC	Federal	Federal 215	71.0	3371	75.0	3534
IMR 7828	Federal	Federal 215	72.0	3338	76.0	3531
IMR 7977	Federal	Federal 215	70.5	3201	77.5	3519
Alliant Reloder 25	Federal	Federal 215	73.0	3270	77.0 C	3478
Hodgdon Retumbo	Federal	Federal 215	75.0	3226	77.0 C	3329
Vihtavuori N560	Federal	Federal 215	72.0	3062	76.0	3294

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load