



270 Winchester

.277"	270
Weight (grains)	TNT@ HP
Ballistic Coefficient	90
Sectional Density	0.303
COAL Tested	0.168
Speer Part No.	3.170"
	1446

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 16	Federal	Federal 210	56.8	3432	60.8 C	3656
Alliant Reloder 17	Federal	Federal 210	55.1	3330	61.0	3653
Alliant Power Pro 2000-MR	Federal	Federal 210	54.0	3515	56.6	3639
Alliant AR-Comp	Federal	Federal 210	47.8	3351	51.8	3603
Winchester 760	Winchester	CCI 250	53.0	3356	59.0	3579
Hodgdon Varget	Winchester	CCI 200	51.5	3302	55.5	3576
Alliant Reloder 15	Winchester	CCI 200	51.0	3230	55.0	3565
Hodgdon H380	Winchester	CCI 250	55.0	3277	59.0	3512
IMR 4064	Winchester	CCI 200	51.0	3155	55.0	3494
Vihtavuori N140	Winchester	CCI 200	50.0	3143	54.0	3451
Alliant Reloder 19	Winchester	CCI 200	60.0	3090	64.0 C	3398
IMR 4831	Winchester	CCI 250	58.0	3149	62.0 C	3329
Accurate 3100	Winchester	CCI 250	58.0	3039	62.0 C	3264

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load