



270 Winchester Short Magnum

.277"	270
	HP
Weight (grains)	100
Ballistic Coefficient	0.201
Sectional Density	0.186
COAL Tested	2.730"
Speer Part No.	1447

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
IMR 4064	Winchester	CCI 200	58.0	3451	62.0	3645
IMR 4350	Winchester	CCI 200	66.0	3426	70.0	3637
Alliant Reloder 16	Federal	Federal 215	60.4	3207	67.0	3614
Hodgdon Varget	Winchester	CCI 200	57.0	3433	61.0	3613
IMR 4320	Winchester	CCI 200	58.0	3381	62.0	3611
Alliant Reloder 17	Federal	Federal 215	59.8	3179	66.2	3606
IMR 4895	Winchester	CCI 200	57.0	3387	61.0	3600
Alliant Reloder 15	Winchester	CCI 200	58.0	3373	62.0	3564
Alliant Power Pro 2000-MR	Federal	Federal 215	56.0	3229	62.0	3517
Alliant Power Pro Varmint	Federal	Federal 215	52.2	3287	56.4	3457
Hodgdon CFE 223	Federal	Federal 215	52.9	3217	58.4	3455
Alliant AR-Comp	Federal	Federal 215	49.6	3264	54.2	3454
IMR 8208 XBR	Federal	Federal 215	47.3	3189	52.4	3432
Ramshot TAC	Federal	Federal 215	49.9	3260	53.9	3409
Accurate 5744 (reduced load)	Winchester	CCI 200	25.0	2010	26.0	2075

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load