



30-06 Springfield

.308"	30 HP	30 SPFN Hot- Cor®
Weight (grains)	130	130
Ballistic Coefficient	0.244	0.212
Sectional Density	0.196	0.196
COAL Tested	3.060"	3.045"
Speer Part No.	2005	2007

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Power Pro 2000-MR	Federal	Federal 210	51.2	2928	56.6	3192
Alliant Reloder 15	Federal	Federal 210	49.5	2862	54.7	3165
Alliant AR-Comp	Federal	Federal 210	46.5	2915	51.4	3149
IMR 8208 XBR	Federal	Federal 210	45.5	2905	50.6	3120
Alliant Power Pro Varmint	Federal	Federal 210	44.6	2841	49.3	3064
Accurate 2460	Winchester	CCI 250	47.5	2805	51.0	3031
IMR 4064	Winchester	CCI 200	51.0	2802	55.0	3022
Hodgdon H414	Winchester	CCI 250	56.0	2787	60.0	3012
Hodgdon Varget	Winchester	CCI 200	51.0	2771	55.0	3006
Accurate 2015	Winchester	CCI 200	45.0	2803	49.0	3004
IMR 3031	Winchester	CCI 200	48.5	2678	52.5	3003
Hodgdon H335	Winchester	CCI 250	50.0	2758	54.0	2979
IMR 4895	Winchester	CCI 200	47.5	2728	51.5	2937
Winchester 748	Winchester	CCI 250	51.0	2728	55.0	2910
Hodgdon BL-C(2)	Winchester	CCI 250	49.0	2699	53.0	2894
Vihtavuori N140	Winchester	CCI 200	48.0	2671	52.0	2868
Hodgdon H4895	Winchester	CCI 200	45.0	2654	49.0	2764
Hodgdon H322	Winchester	CCI 200	43.0	2546	47.0	2757
Accurate 5744 (reduced load)	Winchester	CCI 200	25.0	1819	27.0	1949

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load