



30-06 Springfield

.308"	30 Spitzer SP Hot- Cor®
Weight (grains)	200
Ballistic Coefficient	0.478
Sectional Density	0.301
COAL Tested	3.295"
Speer Part No.	2211

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 26	Federal	Federal 210	52.2	2408	57.8 C	2667
Hodgdon H4350	Winchester	CCI 200	53.0	2358	57.0 C	2582
Alliant Reloder 23	Federal	Federal 210	49.6	2357	54.8 C	2580
Alliant Reloder 16	Federal	Federal 210	46.7	2354	51.7	2578
Alliant Power Pro 4000-MR	Federal	Federal 210	48.1	2370	53.2	2575
Alliant Reloder 17	Federal	Federal 210	45.4	2324	50.4	2561
IMR 7977	Federal	Federal 210	53.9	2303	59.7 C	2546
Hodgdon H4350	Federal	Federal 210	45.8	2322	50.8	2528
Alliant Reloder 22	Winchester	CCI 200	54.0	2281	58.0 C	2525
Alliant Reloder 25	Winchester	CCI 200	58.0	2378	60.0 C	2506
Hodgdon H414	Winchester	CCI 250	49.0	2339	53.0	2477
IMR 4350	Winchester	CCI 200	50.0	2265	54.0	2473
Hodgdon H4831SC	Winchester	CCI 200	53.0	2236	57.0 C	2471
IMR 4831	Winchester	CCI 200	52.0	2302	56.0 C	2453
Vihtavuori N160	Winchester	CCI 200	50.0	2214	54.0	2408
Alliant Reloder 15	Winchester	CCI 200	43.0	2219	47.0	2393
Hodgdon H1000	Winchester	CCI 200	57.0	2167	61.0 C	2393
Hodgdon H380	Winchester	CCI 250	46.0	2177	50.0	2382
Winchester 760	Winchester	CCI 250	47.0	2258	51.0	2369
Alliant Reloder 19	Winchester	CCI 200	51.0	2173	55.0	2356
IMR 4064	Winchester	CCI 200	42.0	2161	46.0	2332
IMR 4198 (reduced load)	Winchester	CCI 200	27.0	1723	31.0	1998

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load