



30-30 Winchester

.308"	30
	Plinker® SPRN
Weight (grains)	100
Ballistic Coefficient	0.144
Sectional Density	0.151
COAL Tested	2.345"
Speer Part No.	1805

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Accurate 2200	Federal	Federal 210	32.9	2760	35.7	2921
Accurate LT-32	Federal	Federal 210	32.7	2663	35.7 C	2873
Alliant Reloder 7	Winchester	CCI 200	31.0	2506	35.0	2865
Hodgdon H322	Winchester	CCI 200	33.0	2419	37.0	2798
Alliant Power Pro 1200-R	Federal	Federal 210	29.5	2642	32.1	2788
Alliant Reloder 10X	Federal	Federal 210	31.2	2641	33.6	2775
Accurate 2015	Winchester	CCI 200	31.0	2409	35.0	2721
IMR 4064	Winchester	CCI 200	33.5	2204	37.5 C	2581
Hodgdon BL-C(2)	Winchester	CCI 250	34.0	2203	38.0	2549
Winchester 748	Winchester	CCI 250	36.0	2138	40.0 C	2534
Vihavuori N133	Winchester	CCI 200	28.0	2169	32.0	2451
Hodgdon H4895	Winchester	CCI 200	31.0	2077	35.0	2433
Hodgdon H380	Winchester	CCI 250	36.0	1989	40.0 C	2359

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load