



30-30 Winchester

.308"	30
	SPFN Hot-Cor®
Weight (grains)	170
Ballistic Coefficient	0.298
Sectional Density	0.256
COAL Tested	2.550"
Speer Part No.	2041

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Power Pro 2000-MR	Federal	Federal 210	34.1	2133	37.5	2318
Hodgdon LEVERevolution	Federal	Federal 210	32.4	2111	35.6	2297
Hodgdon CFE 223	Federal	Federal 210	32.9	2102	36.2	2290
Alliant AR-Comp	Federal	Federal 210	27.5	1982	30.4	2166
Winchester 748	Winchester	CCI 250	30.0	1843	34.0	2145
Alliant Power Pro Varmint	Federal	Federal 210	28.5	2020	30.7	2143
Alliant Reloder 15	Federal	Federal 210	28.5	1875	31.7	2122
Hodgdon Varget	Winchester	CCI 200	27.0	1625	31.0	2027
Hodgdon H322	Winchester	CCI 200	25.0	1686	29.0	2025
Hodgdon H335	Winchester	CCI 250	27.0	1670	31.0	2007
Vihavuori N140	Winchester	CCI 200	27.0	1643	31.0	2002
IMR 3031	Winchester	CCI 200	25.5	1702	29.5	1994
Alliant Reloder 10X	Winchester	CCI 200	22.5	1646	26.5	1990
IMR 4064	Winchester	CCI 200	27.0	1654	31.0	1982
Winchester 760	Winchester	CCI 250	31.0	1634	35.0	1963
Hodgdon H414	Winchester	CCI 250	31.0	1596	35.0	1942
IMR 4350	Winchester	CCI 200	30.5	1566	34.5	1930
IMR 4895	Winchester	CCI 200	25.0	1614	29.0	1892
Accurate 2460	Winchester	CCI 250	24.0	1587	28.0	1884

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load