



## 30-40 Krag

.308"	30 HP	30 SPFN Hot- Cor®
Weight (grains)	130	130
Ballistic Coefficient	0.244	0.213
Sectional Density	0.196	0.196
COAL Tested	2.865"	2.865"
Speer Part No.	2005	2007

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
IMR 4064	Winchester	CCI 200	42.0	2438	46.0	2694
IMR 4320	Winchester	CCI 200	42.0	2385	46.0	2632
Hodgdon H380	Winchester	CCI 250	44.0	2406	48.0	2622
IMR 3031	Winchester	CCI 200	39.0	2332	43.0	2611
Hodgdon H414	Winchester	CCI 250	47.0	2327	51.0	2582
IMR 4350	Winchester	CCI 200	48.0	2360	52.0	2571
Hodgdon H322	Winchester	CCI 200	33.0	2003	37.0	2253
IMR 4198 (reduced load)	Winchester	CCI 200	25.0	1983	29.0	2209

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*