



30-40 Krag

.308"	30 Spitzer SP Hot- Cor®
Weight (grains)	200
Ballistic Coefficient	0.478
Sectional Density	0.301
COAL Tested	3.089"
Speer Part No.	2211

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
IMR 4350	Winchester	CCI 200	42.0	1926	44.0	2034
IMR 4831	Winchester	CCI 200	43.0	1909	45.0	2017
IMR 4895	Winchester	CCI 200	34.0	1857	36.0	1976
IMR 3031	Winchester	CCI 200	31.0	1715	35.0	1974
IMR 4064	Winchester	CCI 200	35.0	1837	37.0	1953
Winchester 760	Winchester	CCI 250	38.0	1714	42.0	1942
Hodgdon H414	Winchester	CCI 250	38.0	1742	40.0	1849
IMR 4198 (reduced load)	Winchester	CCI 200	24.0	1509	28.0	1762

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load