



speer®
bullets

300 AAC Blackout

.308"	30
	HP
Weight (grains)	130
Ballistic Coefficient	0.244
Sectional Density	0.196
COAL Tested	2.060"
Speer Part No.	2005

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Power Pro 300-MP	Lake City	Federal 205	18.7	2002	20.5	2175
Ramshot Enforcer	Lake City	Federal 205	16.4	1977	18.2	2132
Vihtavuori N110	Lake City	Federal 205	16.1	1955	17.9 C	2113
Accurate 5744	Lake City	Federal 205	18.0	1851	19.7 C	2105
IMR 4227	Lake City	Federal 205	17.3	1859	19.0 C	2029
Accurate No. 9	Lake City	Federal 205	13.2	1810	14.6	1944

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load