



speer®
bullets

300 AAC Blackout

.308"	30 Spitzer BTSP	30 Spitzer SP Hot-Cor®	30 Grand Slam® SP/CANN
Weight (grains)	165	165	165
Ballistic Coefficient	0.520	0.444	0.354
Sectional Density	0.248	0.248	0.248
COAL Tested	2.250"	2.250"	2.250"
Speer Part No.	2034	2035	2038

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Hodgdon Lil'Gun	Lake City	Federal 205	18.0	1928	19.5 C	2051
Accurate 5744	Lake City	Federal 205	16.9	1732	18.8 C	1912
Alliant Power Pro 300-MP	Lake City	Federal 205	16.4	1719	18.3	1891
Vihtavuori N120	Lake City	Federal 205	17.5 C	1736	18.7 C	1848
IMR 4227	Lake City	Federal 205	15.9	1678	17.4 C	1827
Vihtavuori N110	Lake City	Federal 205	13.8	1684	15.4	1815
Winchester 296	Lake City	Federal 205	15.1	1705	16.4	1805
Accurate No. 9	Lake City	Federal 205	12.1	1622	13.3	1739
Alliant 2400	Lake City	Federal 205	12.3	1583	13.2	1686

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load